5.250"

## ZIP-STRIP® CONTRATORS PLUS PAINT & FINISH REMOVER

Removes oil based and latex paints, varnish, shellac, lacquer, urethane and polyurethane finish and aids in stain removal. Contains no acid or alkali. Will not harm metal, wood or genuine leather. DO NOT use on plastic, vinyl, asphalt, or rubber flooring, synthetic fabric or foam products. May soften fiberglass.

DIRECTIONS: Wear safety glasses and thick heavy duty rubber gloves. USE CAUTION WHEN OPENING. Apply liberally, brushing in one direction only. Leave on from 10-20 minutes, depending on the number of coats of old finish to be removed. After finish bubbles loose from surface, remove with scraper, steel wool or wash off with a scrub brush or coarse rag and cool water before old finish dries. Do not let softened finish dry. Scraping with a wide-blade putty knife is the preferred method for wood surfaces as water will raise the wood grain. Some finishes such as varnish and latex will not wrinkle or bubble. Pretest for removal time before use. Use old brush - discard after use. Do not use in direct sunlight or on hot surfaces. Do not rush the remover, let Zip-Strip do the work.

FINAL CLEANING: Dip steel wool in remover, scrub surface, then wipe dry with clean cloth. Let dry 24 hours and sand before staining or finishing.

WOOD FLOORS: Apply remover as recommended above. Thoroughly remove all old finish and paint remover from surface and board joints. Allow 24 hours to dry before finishing.

STAINS: To acquire a lighter tone, scrub surface with steel wool and a combination of 8 parts Zip-Strip and 1

CONTAINS: Methylene Chloride (CAS# 75-09-2), Methanol (CAS# 67-56-1), Toluene (CAS# 108-88-3) and Acetone (CAS#67-64-1). Cannot be made non-poisonous. 440 grams VOC per liter of material. VOC vapor pressure 54 mm Hg @ 20° C. This product is non-photochemically reactive.

## POISON & KEEP OUT OF REACH OF CHILDREN / ANIMALS

FIRST AID: IF SWALLOWED, do not induce vomiting. Get medical attention immediately. If you experience difficulty breathing, leave area, obtain fresh air. If difficulty continues, get medical assistance immediately. Avoid contact with eyes, skin and clothing. EYE CONTACT: Immediately flush thoroughly with water for at least 15 minutes, get medical attention at once. SKIN CONTACT: Flush with plenty of water for at least 15 minutes. Wash thoroughly with soap and water. If irritation persists, seek advice of physician. Remove contaminated clothing and shoes. Wash clothing before reuse.

TRANSPORT AND STORE in upright position only. Never store or transport in an area where sun or heat exposure may cause temperature of product to elevate above normal ambient conditions, this may cause product to expand, causing product to leak or rupture container.

IF SPILLED, contain material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal 33-644ZIPEXP 00916

DISPOSAL: Clean up rags, papers and waste promptly and move outdoors. Allow solvent to evaporate, then dispose of in metal container in accordance with local, state and federal regulations.

Edmonton

**CCCR** Changes

Changes to Artwork

<u>\</u>

197 5G Milton, ON L9T 5G Tel: 905.878.5544

www.recochem.con