33-604ZIPEXP

Instrucciones: La pasta de consistencia semi-hace posible su uso en superficies verticales y horizontales. Quita esmalte, látex y pintura acrílica, barniz, laca, lacquear, uretano, poliuretano, epoxi y ayudas termina en remover manchas. La utilización de este producto al aire libre si es posible. Si debe utilizar en interiores, abra todas las puertas y ventanas o usar otros medios para garantizar la circulación de aire fresco durante la aplicación y el secado. Quitar con espátula o lana de acero antes de secar. LLeve quantes protectores y ropa protector. Trabaje en una region bien ventilada. Limpie la superficie a fondo con un paño limpio y dejar secar durante la noche. Próximo, alise con papel de lija antes de colorar o aplicar acabado nuevo.

Vapores nocivos. Podrían afectar el cerebro o el sistema nervioso, provocando mareos, cefaleas o náuseas. Irrita la piel, los oios, la nariz y la garganta. Disminuve la capacidad de transporte de oxígeno del organismo. Podría ser nocivo si se absorbiera a través de la piel. No puede evitarse que sea venenoso. AVISO: hay informes que asocian la sobreexposición repetida y prolongada (por razones laborales) a solventes, con lesiones permanentes en cerebro y sistema nervioso. El mal uso intencional la concentración e inhalación deliberada del contenido podría resultar nocivo o fatal. Contiene cloruro de metileno, que se ha demostrado es cancerígeno para ciertos animales de laboratorio. El riesgo para la salud depende del grado y duración de la exposición. Mantenga alejado de calor, chispas y llamas. Los vapores podrían provocar un fuego espontáneo. No fume. Apague todas las llamas y luces piloto; apague hornos, calentadores, motores eléctricos y toda fuente de ignición durante el uso del producto y hasta evacuar todos los vapores. Abra puertas y ventanas para ventilar y evitar que se acumulen los vapores.

Use únicamente con la ventilación adecuada. Evite inhalar vapores o el producto atomizado. Asegure la entrada de aire fresco durante la aplicación y el secado. Si experimenta lagrimeo de ojos, dolor de cabeza o mareo, o si el monitoreo del aire muestra que los niveles de vapor / emisiones están por encima de los niveles aceptables, use un respirador apropiado de su tamaño (aprobado por NIOSH) durante y después de la aplicación. Siga las instrucciones de uso del fabricante del respirador. Evite el contacto con los ojos, la piel y la ropa. Lávese bien después de manipular el producto.

Primeros auxilios: En caso de producirse contacto con los ojos o la piel, lávese inmediatamente con agua en abundancia durante al menos 15 minutos. Quítese la ropa y los zapatos contaminados. Obtenga atención médica de inmediato. Lave la ropa antes de volver a usarla. Si tuviese dificultades para respirar, abandone el área y vava a un sitio con aire fresco. Si continuara con dificultades para respirar obtenga atención médica de inmediato. Si se ingiriera, no induzca el vómito. Obtenga atención médica de inmediato.

VENENO. 🙊 MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.

Si se derramara, contenga el producto derramado y quítelo con un material inerte absorbente. Deshágase del material absorbente contaminado, del recipiente y del contenido no usado de acuerdo con los reglamentos locales, estatales y federales

272001

NON-FLAMMABLE



PREMIUM **PAINT & FINISH** REMOVER

REMOVES PAINT IN 10 MINUTES!

WATER-RINSABLE • SEMI-PASTE **USE ON WOOD, METAL, AND MASONRY**

DANGER 😤 POISON VAPOR HARMFUL. MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. CAUSES EYE AND SKIN IRRITATION. Read Cautions and HEALTH HAZARD INFORMATION elsewhere on label.

128 FL. OZ. (ONE GALLON) • 3.78 L

consult their physician before use. use and until all vapors are gone.

and water after handling. Cannot be made non-poisonous. container.

19.776"

HEALTH HAZARD INFORMATION

Vapor Harmful. Contains methylene chloride which has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure. May affect the brain or nervous system causing dizziness, headache or nausea, REDUCES THE **BLOOD'S OXYGEN-CARRYING CAPACITY.**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. People having or suspected of having heart trouble, pulmonary disorder or pregnant women should

Contact with flame or hot surface may produce toxic/corrosive gases. Keep away from heat, sparks and flame. Vapor may cause flash fire. Do not smoke. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Extinguish all flames and pilot lights, turn off stoves, heaters, electric motors, clothes dryers, electric paint strippers and other sources of ignition during

Use only with adequate ventilation. Use this product outdoors, if possible. If you must use indoors, open all windows and doors or use other means to ensure fresh air movement during application and drying. If you experience eye watering, headache or dizziness, or if workplace exposure monitoring indicates methylene chloride levels cannot be controlled below the established OSHA exposure limits (29 CFR 1910.1050), then appropriate respiratory protection must be provided. Obtain professional advice before using respiratory protection. A dust mask does not provide protection against vapors. Do not use in basement or other unventilated area. Do not breathe vapors or mist. Avoid contact with eyes, skin and clothing. Causes eye, nose, throat and skin irritation. Avoid prolonged or repeated contact with skin. May be harmful if absorbed through skin. Wash thoroughly with soap

Open container carefully and close after each use. Clean up rags, papers and waste promptly. Allow solvent to evaporate then dispose of in a metal

ZIP-STRIP[®] PREMIUM PAINT & FINISH REMOVER Removes 2-3 coats in 10 minutes; 12+ coats in 60 minutes or less.

REMOVES: Enamel, latex and acrylic paint, varnish, lacquer, shellac, urethane, polyurethane, epoxy finishes and aids in stain removal. Will not raise the grain of wood, harm metal or genuine leather. Do not use on synthetic fabrics, rayon, nylon, linoleum, asphalt, foam products or rubber tile. May soften fiberglass or plastic.

DIRECTIONS: Wear safety glasses and thick heavy duty rubber gloves. USE CAUTION WHEN OPENING. Apply liberally, brushing in one direction only. Leave on from 10-20 minutes, depending on the number of coats of old finish to be removed. After finish bubbles loose from surface, remove with scraper, steel wool or wash off with a scrub brush or coarse rag and cool water before old finish dries. Do not let softened finish dry. Scraping with a wide-blade putty knife is the preferred method for wood surfaces as water will raise the wood grain. Some finishes such as varnish, epoxy and latex will not wrinkle or bubble. Pretest for removal time before use. Use old brush discard after use. Do not use in direct sunlight or on hot surfaces. Do not rush the remover, let Zip-Strip do the

ON WOOD FLOORS: Clean all remover from cracks and joints. Allow to dry thoroughly (at least 24 hours) before refinishing.

FINAL CLEAN-UP: Use fine steel wool dipped in Zip-Strip or paint thinner. Wipe surface thoroughly with clean cloth. Allow to dry overnight before finishing.

STAINS: To acquire a lighter tone, scrub surface with steel wool and a combination of 8 parts Zip-Strip and 1 part bleach

POISON Se KEEP OUT OF REACH OF CHILDREN / ANIMALS

FIRST AID: If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty breathing, leave area, obtain fresh air. If difficulty continues, get medical assistance immediately. Avoid contact with eyes, skin and clothing. EYE CONTACT: Immediately flush thoroughly with water for at least 15 minutes, get medical attention at once.

SKIN CONTACT: Flush with plenty of water for at least 15 minutes. Wash thoroughly with soap and water. If irritation persists, seek advice of physician. Remove contaminated clothing and shoes. Wash clothing before reuse. TRANSPORT AND STORE in upright position only. Never store or transport in an area where sun or heat exposure may cause temperature of product to elevate above normal ambient conditions, this may cause product to expand, causing product to leak or rupture container.

DISPOSAL: Clean up rags, papers and waste promptly and move outdoors. Allow solvent to evaporate, then dispose of in metal container in accordance with local, state and federal regulations.

CONTAINS: Methylene Chloride (CAS# 75-09-2), Methanol (CAS# 67-56-1) and Mineral Spirits (CAS# 8052-41-3). VOC less than 50%. This product is non-photochemically reactive.

WARNING - Cancer - www.P65Warnings.ca.gov/product

RECOCHEM INC.

Montréal Toronto Edmonton Vancouver H4T 1P4 L9T 5G7 T9E 7X6 V3C 4P2 www.recochem.com MADE IN CANADA

Zip-Strip® is a registered trademark of Recochem Inc. © 2014 Recochem Inc., All Rights Reserved

DIRECTION TO PRINTER: NIA				DRAFT # 1	DRAFT # 1 REVIEW # FINAL	
	COLOURS AND COATINGS	APPLICATION Illustrator CS5	or CS5		PURCHASING/LOCATIONS:	
	couleurs et couchages	FONTS Arial ar	Arial and Arial Black		Shezana Jankovic	5
		PRODUCT NAME Zip-Strip	PRODUCT NAME Zip-Strip Premium Paint & Finish Remover		Cari-Iviae Sampaio/Kanuy Stepmenson Wayne Popoff	liosii
cochem Your Partner in Formulating Solutions	Pantone YLW BLACK	PRODUCT CODE CAN-33604ZIP	04ZIP REVISION CODE: FRONT 0916 BACK: -	CK: -	Irvin McDonell	
0775 Holosto Croccont		DIMENSIONS 19.776	19.776 width x 9.630 height		Christian Tremblay	
0/23 HOUGALE CLESCENIC	Pantone XXX Pantone XXX	UPC CODE	0-38514-72001-5		Milton	
			Armapro 🗌 BellePak 🔲 Cascades 🗌 Datamark 🔲 Emballages 🗍 Fastik 🛛 Jgraphx 🛛	Fastik 🗌 Jgraphx 🗌	Vancouver	
1el: 905.8/8.cub	Pantone XXX Pantone XXX		Labelink 🗾 Luma 🔄 Mega 🔄 Polycel 🔄 ProArt 🔄 Propals 🗌 Other	Propals 🗌 Other 📃	Edmonton	
www.recochem.com			LABEL TYPE Paper 🛛 Foil 🗌 Sleeve 🗌 Carton 🗌 CARTON TYPE Oyster 🛄 Kraft 🛄 N/A 🗾	- 🗌 Kraft 🗌 N/A 🗾	APPROVED BY NELIA DOCOUTO	
	Pantone XXX Pantone XXX	DATE REVISED	September 22, 2016			
		DATE APPROVED			DATE APPROVED	
Montréal	Australia	Belgium	Edmonton	Vano	Vancouver	
REASON FOR ART REQUEST: 📃 New Art	>	Changes to Artwork	New Die Line		Supplier change	
	Othor					