

ZIP-STRIP® INDUSTRIAL PAINT & FINISH REMOVER

REMOVES: Enamel, latex and acrylic paint, varnish, lacquer, shellac, urethane, polyurethane, epoxy finishes and aids in stain removal. Will not raise the grain of wood, harm metal or genuine leather. Do not use on synthetic fabrics, rayon, nylon, linoleum, asphalt, foam products or rubber tile. May soften fiberglass or plastic.

DIRECTIONS: Wear safety glasses and thick heavy duty rubber gloves. **USE CAUTION WHEN OPENING.** Apply liberally, brushing in one direction only. Leave on from 10-20 minutes, depending on the number of coats of old finish to be removed. After finish bubbles loose from surface, remove with scraper, steel wool or wash off with a scrub brush or coarse rag and cool water before old finish dries. Do not let softened finish dry. Scraping with a wide-blade putty knife is the preferred method for wood surfaces as water will raise the wood grain. Some finishes such as varnish, epoxy and latex will not wrinkle or bubble. Pretest for removal time before use. Use old brush - discard after use. Do not use in direct sunlight or on hot surfaces. Do not rush the remover, let Zip-Strip do the work. **ON FLOORS:** Clean all remover from cracks and joints. Allow to dry thoroughly (at least 24 hours) before refinishing. FINAL CLEAN-UP: Use fine steel wool dipped in Zip-Strip or paint thinner. Wipe surface thoroughly with clean cloth. Allow to dry overnight before finishing. STAINS: To acquire a lighter tone, scrub surface with steel wool and a combination of 8 parts Zip-Strip and 1 part bleach.

CONTAINS: Methylene Chloride (CAS# 75-09-2), Methanol (CAS# 67-56-1), Mineral Spirits (CAS# 8052-41-3) and Nonylphenol Polyethylene Glycol Ether (CAS# 9016-45-9). Cannot be made non-poisonous. VOC less than 50%. This product is non-photochemically reactive.

POISON KEEP OUT OF REACH OF CHILDREN / ANIMALS

FIRST AID: If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty breathing, leave area, obtain fresh air. If difficulty continues, get medical assistance immediately. Avoid contact with eyes, skin and clothing. EYE CONTACT: Immediately flush thoroughly with water for at least 15 minutes, get medical attention at once. SKIN CONTACT: Flush with plenty of water for at least 15 minutes. Wash thoroughly with soap and water. If irritation persists, seek advice of physician. Remove contaminated clothing and shoes. Wash clothing before reuse.

△WARNING - Cancer - www.P65Warnings.ca.gov/product

TRANSPORT AND STORE in upright position only. Never store or transport in an area where sun or heat exposure may cause temperature of product to elevate above normal ambient conditions, this may cause product to expand, causing product to leak or rupture container.

IF SPILLED, contain material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

DISPOSAL: Clean up rags, papers and waste promptly and move outdoors. Allow solvent to evaporate, then dispose of in metal container in accordance with local, state and federal regulations.



Vancouver Fastik **CCCR** Changes Changes to Artwork **** 8725 Holgate Crescer Milton, ON L9T 5G7 Tel: 905.878.5544 www.recochem.com