



303 Fabric Guard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 7/1/2012 Revision date: 5/27/2022 Supersedes: 7/27/2021 Version: 3.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : 303 Fabric Guard
Synonym : 0700423
Part numbers : 30601; 30603; 30604CSR; 30605CSR; 30606CSR; 30607; 30606; 30605; 30604; 30616; 30618; 30655; 30674; 30677; 130764; 130616; 130606

1.2. Recommended use and restrictions on use

Recommended use : Read label before use.
Restrictions on use : Use per the label directions

1.3. Supplier

Manufacturer

Gold Eagle Co
4400 S Kildare Ave
Chicago, IL, 60632-4372
T 773-376-4400
<https://www.goldeagle.com/>

1.4. Emergency telephone number

Emergency number : INFOTrac: 1-800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Specific target organ toxicity (repeated exposure) Category 1	H372	Causes damage to organs through prolonged or repeated exposure
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.

303 Fabric Guard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P314 - Get medical advice/attention if you feel unwell.
P331 - Do NOT induce vomiting.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	0 – 92	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Mineral spirits	-	0 – 5	Not classified
n-Butyl acetate	CAS-No.: 123-86-4	0 – 2.4	Flam. Liq. 3, H226 STOT SE 3, H336
Medium aliphatic solvent naphtha (C9-12)	CAS-No.: 64742-88-7	1 – 5	STOT RE 1, H372 Asp. Tox. 1, H304
polytetrafluoroethylene	CAS-No.: 9002-84-0	0 – 1.6	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after ingestion : Risk of lung edema.

303 Fabric Guard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

303 Fabric Guard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

303 Fabric Guard

No additional information available

Mineral spirits

No additional information available

Distillates (petroleum), hydrotreated light (64742-47-8)

No additional information available

n-Butyl acetate (123-86-4)

No additional information available

Medium aliphatic solvent naphtha (C9-12) (64742-88-7)

No additional information available

polytetrafluoroethylene (9002-84-0)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



303 Fabric Guard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following colour(s): White-grey
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Odourless
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 150 °C
Flash point	: ≥ 122 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: < 0.1
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 0.5 mm Hg
Relative vapor density at 20 °C	: 5.3
Relative density	: 0.85
Density	: 7.8 lb/gal
Solubility	: Water: < 0.1 %
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 3 mm ² /s (40 °C)
Viscosity, dynamic	: No data available
Explosion limits	: Lower explosion limit: 0.6 g/m ³ Upper explosion limit: 5.5 g/m ³
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content	: 100 VOC Exempt solvents
-------------	---------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

303 Fabric Guard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

n-Butyl acetate (123-86-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Medium aliphatic solvent naphtha (C9-12) (64742-88-7)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: 3 mm ² /s (40 °C)
Symptoms/effects after ingestion	: Risk of lung edema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

n-Butyl acetate (123-86-4)

Partition coefficient n-octanol/water (Log Kow)	1.78
---	------

polytetrafluoroethylene (9002-84-0)

Bioaccumulative potential	No test data available.
---------------------------	-------------------------

12.4. Mobility in soil

polytetrafluoroethylene (9002-84-0)

Ecology - soil	No (test)data on mobility of the substance available.
----------------	---

303 Fabric Guard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA No	: UN1268
UN-No. (TDG)	: UN1268
UN-No. (IMDG)	: 1268
UN-No. (IATA)	: Not applicable


14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Petroleum products, n.o.s
Proper Shipping Name (TDG)	: Hydrocarbons, Liquid, n.o.s.
Proper Shipping Name (IMDG)	: HYDROCARBONS, LIQUID, N.O.S.
Proper Shipping Name (IATA)	: Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT)	: LTD QTY
Hazard labels (DOT)	: LTD QTY



TDG

Transport hazard class(es) (TDG)	: 3
----------------------------------	-----

IMDG

Transport hazard class(es) (IMDG)	: 3
Hazard labels (IMDG)	: 3



IATA

Transport hazard class(es) (IATA)	: Not applicable
-----------------------------------	------------------

303 Fabric Guard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.4. Packing group

Packing group (DOT)	: III
Packing group (TDG)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: Not applicable

14.5. Environmental hazards

Other information	: No supplementary information available.
-------------------	---

14.6. Special precautions for user

DOT

UN-No.(DOT)	: UN1268
DOT Special Provisions (49 CFR 172.102)	: 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

TDG

UN-No. (TDG)	: UN1268
Emergency Response Guide (ERG) Number	: 128

IMDG

Limited quantities (IMDG)	: 1 L
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS

303 Fabric Guard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Stowage category (IMDG) : B
Flash point (IMDG) : 122F (50C)
Properties and observations (IMDG) : Immiscible with water.

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Mineral spirits		Not present	-	
Distillates (petroleum), hydrotreated light	64742-47-8	Present	Active	
n-Butyl acetate	123-86-4	Not present	-	
Medium aliphatic solvent naphtha (C9-12)	64742-88-7	Not present	-	
polytetrafluoroethylene	9002-84-0	Not present	-	

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/27/2022

Full text of H-phrases	
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H336	May cause drowsiness or dizziness
H372	Causes damage to organs through prolonged or repeated exposure

303 Fabric Guard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Indication of changes:			
Section	Changed item	Change	Comments
1		Added	Part Numbers: 130674; 130616; 130606
14		Modified	Added " UN1268, Hydrocarbons, Liquid, n.o.s., 3, III

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.