



## ENERTITE® G Series Open-cell Resin Component

(Credentials below when combined with BASF  
ELASTOSPRAY® 8000A isocyanate)



**Shelf-life: 6 months**  
**Stored at 50-80°F**

### Processing Details:

Machine Temps: 105-135F  
Machine Pressures: 1150-1450 psi  
Spray Pressures: 900-1200 psi

**Bring drums to 70°F before  
pumping and attempt to maintain for ease**



**BASF Corporation**  
ENERTITE G

**CODE COMPLIANCE**

**CERTIFIED TO:**

ASTM E84  
Flame Spread Index 25 or less  
Smoke Developed Index 450 or less;  
ASTM E96/E96M; ASTM E283; ASTM E970  
ICC-ES AC377; ICC-ES AC377, Appendix X;  
NFPA 285; NFPA 286

**Intertek** **Intertek**

**CCRR-1032**  
Control No: 5007128 (HOUSTON)

Refer to the Intertek Directory of Building Products  
(<https://bpdirectory.intertek.com>)



**ESR-3102**  
Flame Spread Index ≤25  
Smoke Development Index ≤450

Inspection Agency:  
Underwriters Laboratories



FOAMED PLASTIC INGREDIENT  
FIRE RESISTANCE CLASSIFICATION  
SEE UL FIRE RESISTANCE DIRECTORY

<28P2>

<R9865>



ENERTITE® is a registered trademark of BASF Corporation.  
ENERGY STAR® is a registered trademark of the United States Department of Energy.  
UL and UL logos are trademarks of UL LLC.

Rev. 04.22.2024\_JG



## ENERTITE® G Series Open-cell Resin Component

(Credentials below when combined with BASF  
ELASTOSPRAY® 8000A isocyanate)



**Shelf-life: 6 months**  
**Stored at 50-80°F**

### Processing Details:

Machine Temps: 105-135F  
Machine Pressures: 1150-1450 psi  
Spray Pressures: 900-1200 psi

**Bring drums to 70°F before  
pumping and attempt to maintain for ease**



**BASF Corporation**  
ENERTITE G

**CODE COMPLIANCE**

**CERTIFIED TO:**

ASTM E84  
Flame Spread Index 25 or less  
Smoke Developed Index 450 or less;  
ASTM E96/E96M; ASTM E283; ASTM E970  
ICC-ES AC377; ICC-ES AC377, Appendix X;  
NFPA 285; NFPA 286

**Intertek** **Intertek**

**CCRR-1032**  
Control No: 5007128 (HOUSTON)

Refer to the Intertek Directory of Building Products  
(<https://bpdirectory.intertek.com>)



**ESR-3102**  
Flame Spread Index ≤25  
Smoke Development Index ≤450


Inspection Agency:  
Underwriters Laboratories



FOAMED PLASTIC INGREDIENT  
FIRE RESISTANCE CLASSIFICATION  
SEE UL FIRE RESISTANCE DIRECTORY

<28P2>

<R9865>



ENERTITE® is a registered trademark of BASF Corporation.  
ENERGY STAR® is a registered trademark of the United States Department of Energy.  
UL and UL logos are trademarks of UL LLC.

Rev. 04.22.2024\_JG